

OpenUV380 Instructions by Ian Spencer DJ0HF v1.1M 3.9.2022

Uploading your code plug to the UV380/RT3S

First use your fingertip to pull down the rubber cover on the right hand side of the radio to expose the mic and earphone sockets. Plug one end of the programming cable into the mic and earphone sockets and the other end into a USB port on your computer. You must use a cable designed for the TYT MD380 or UV380, the cable from a GD77 or similar radio will not work. Then turn the UV380/RT3S on in the normal way as if you were going to use it. It is very important to connect your radio to the computer before turning it on or the radio may not be recognised by the computer.

Set the focus to your desktop and type o until you find the OpenCPS short cut and then hit Enter.

The CPS program will start and automatically retrieve the last code-plug you created so you don't have to search for it.

Type Ctrl+w and a new window will open asking if you want to overwrite the code plug and you are on the yes button so hit Enter because you want to upload the code plug. The writing of the code-plug will automatically start. Generally it takes about 20 or 30 seconds and when finished my computer give a burble sound. If unsure wait a couple of minutes.

Type Alt+F4 and a new window will open asking if you want to save the code plug before exiting, you are on the yes button and you can either hit enter to save and exit or tab to the no field and hit enter to exit without saving.

You can now turn off the radio and disconnect it from the computer, your code plug is now in the UV380/RT3S and ready to use.